RADIATION-PROOF PARTITION SYSTEM

VarioShield[Basic] & VarioShield[Plus]

VAR102-11-75-1.0 lead

Radiation-proof, lightweight partition wall, with on one side a VarioShield fitted with lead and on the other side one mounted standard plasterboard.

VarioShield has developed an innovative system, VarioShield[Plus]. These small (1200 mm long, 600 mm wide) VarioShield[Plus] panels have a special overlap that ensures you can build walls that are guaranteed radiation proof. These panels are also easy to handle thanks to their low weight.



VarioShield[Plus]

SYSTEM PERFORMANCE	System thickness [mm]	System weight [kg/m²]
	102	32
Fire resistance wall (Dutch market DGMR)	EI [minutes]	Max. height fire performance
	EI30	3600
Sound insulation	Sound insulation Rw ($C;C_{Tr}$) Simulation	
	44dB (-4;-12)	
Maximum height stability (DIN 18183-1)	Field of application I [mm]	Field of application II [mm]
	4500	3750
Radiation proof	Applus RTD Benelux Report	
	9287-112321/001/1/2015 rev. 0	



System structure:

1. VarioShield[Basic] or VarioShield[Plus] with 1.0 mm lead
2. Standard plasterboard 12.5 mm
3. Self-adhesive lead strips 1.0 mm
4. C-profile 75 mm centre-to-centre 600 mm
5. U-profile 75 mm
6. U-profile attachment on building construction
7. VarioShield screw 45 mm, centre-to-centre 250 mm
8. Insulation not necessary
9. Acoustic felt

For more information, please refer to our installation advice, documentation, reports and website.

VARIOSHIELD bv
Korenmaat 12c
9405 TJ Assen

T (+) 31 592 330123
E info@varioshield.com
W www.varioshield.com

Chamber of Commerce number: 71981128
Bank: IBAN NL73RABO0311965679 BIC RABONL2U
VAT: NL858927081 B01